

The ClearOne Ceiling Microphone Array enhances any conferencing application which demands high-quality audio. Easily installed and affordable, the Ceiling Microphone Array delivers exceptional audio quality.

Featuring three wide-range microphones mounted together into a single unit array, the Ceiling Microphone Array provides the rich sound of three individual unidirectional microphones while maintaining full 360-degree coverage.



### Applications



- Medium to Large conference rooms
- Boardrooms
- Overflow areas
- Training Rooms
- Courtrooms
- Distance Learning Centers
- Convention Centers and Hotels



### Features




- Superior Audio Performance
- + Full 360-degree coverage
- + Three unidirectional elements reduce reverberation and noise
- + Design minimizes noise pickup from ceiling sources
- Compatibility
- + Optimized to work with ClearOne mixers - CONVERGE Pro, INTERACT Pro, INTERACT Pro 8i, INTERACT AT
- Expandability
- + Multiple\* ceiling microphone arrays can be connected to any ClearOne mixer for covering a large room space
- Easy Setup
- + Standard CAT5 Ethernet cable runs back to the mixer
- + Designed for quick installation into drop ceiling tiles
- + Includes 12" and 24" drop down cables for varying ceiling heights
- Minimal Visibility
- + Sleek unobtrusive design
- + Free table area while maintaining speech quality and intelligibility
- + Compact size: 3.3" x 1.5" (83.8 mm x 38.1 mm)


\* The number of ceiling microphone arrays depends on the maximum number of microphone inputs supported by the mixer.

## COMPONENTS

Microphone Array




Mounting Assembly



Microphone Cable with Grommet



RJ45 Receptacle to Mixer Adapter Cables



## Functional Specifications

### ACOUSTIC CHARACTERISTICS

Polar Pattern: Cardioid  
 Dynamic Range: 80 dB, 1 kHz @ max SPL  
 Signal/Noise Ratio: 60 dB, 1 kHz @ 1 Pa  
 Frequency Response: 100 Hz - 12 kHz  
 Sensitivity: 114 mV/Pa

### ELECTRICAL CHARACTERISTICS

Element: Fixed-charge back plate permanently polarized condenser  
 Phantom Power Requirement: 12-52 vdc, 2 mA typical  
 Impedance: 200 Ω

### CABLES INCLUDED

12-inch and 24-inch 4-pin mini-XLR drop-down cable  
 25-foot RJ45 male to RJ45 male CAT5e  
 RJ45 receptacle to mixer adapter cable

### MOUNTING

Ceiling tile pass-through mounting assembly  
 Max cable length from array to mixer: 300 ft (91.44m)

### MECHANICAL

Dimensions (H x Dia)  
 3.3" x 1.5"  
 (83.8 mm x 38.1 mm)

### WEIGHT

2.2 lbs (1 kg)

### ENVIRONMENTAL

Operating Temperature  
 -4° to 158° F (-20° to 70° C)

### WARRANTY

2-Year, From date of purchase

### PART NUMBERS

910-001-013-W - White Ceiling Microphone Array kit for CONVERGE Pro and INTERACT Pro (includes RJ45 receptacle to Mini-Phoenix mixer adapter)


910-001-013-B - Black Ceiling Microphone Array kit for CONVERGE Pro and INTERACT Pro (includes RJ45 receptacle to Mini-Phoenix mixer adapter)

910-001-014-W - White Ceiling Microphone Array kit for INTERACT AT (includes RJ45 receptacle to XLR-M mixer adapter)

910-001-014-B - Black Ceiling Microphone Array kit for INTERACT AT (includes RJ45 receptacle to XLR-M mixer adapter)

(Each kit includes Microphone Array Module, Mounting base, 12 and 24 inch drop-down cables, 25 foot RJ45 plenum rated CAT5e cable, RJ45 receptacle to mixer adapter cable.)

### PICK-UP PATTERN



## ClearOne Contacts

### North America

Tel: 801-975-7200  
 Toll Free: 800-945-7730  
 TechSales: 1-800-707-6994  
 Fax: 801-977-0087  
 sales@clearone.com

### Europe & Oceania

Tel: +44 (0) 1189 036 053  
 global@clearone.com

### Asia Pacific

Tel: +852 3590 4526  
 global@clearone.com

### Latin America

Tel: 801-974-3621  
 global@clearone.com

### Middle East

Tel: +852 3590 4526  
 global@clearone.com