



FlexScan® EV2216W



The EIZO EV2216W impresses with a modern, bright and energy-efficient LED backlight. Typical power consumption is only 12 watts. The monitor's EcoView functions also save energy by intelligently adjusting the image brightness to the environment, using Auto EcoView and to the image content with EcoView Optimizer. EcoView Sense switches off the monitor whenever possible. EcoView means maximum user convenience, reduced impact on the environment and minimal operating costs. Connectivity is provided through DisplayPort, DVI-D and D-Sub connections, as well as a USB hub with one upstream port and two downstream ports located on the side panel. The EV2216W is targeted at companies and government agencies, but also attracts interest from private users who want a high-quality monitor.

- ◆ 22" with 16:10 aspect ratio and LED technology in a compact, space-saving design
- ◆ Contrast 1000:1, brightness 250 cd/m²
- ◆ Auto EcoView, EcoView Index, EcoView Sense and EcoView Optimizer for maximum power savings and superb ergonomics
- ◆ Integrated speakers and headphone jack
- ◆ USB hub with one upstream and two downstream ports
- ◆ DisplayPort, DVI-D and D-Sub inputs for digital and analogue connection



EIZO EV2216W

Features

Compact, space-saving design

The sophisticated LCD module has a very narrow border and is designed for an extremely compact housing. The border around the image is no more than 14.3 mm. Power supply and signal interfaces are unobtrusively integrated into the unit.

Outstanding image quality

A resolution of 1680 x 1050 pixels, a contrast ratio of 1000:1 and brightness of 250 cd/m² all ensure first-class image quality with clear graphics and structures as well as sharp text contours. No matter if you're sitting directly in front of the display or at an angle, the entire screen always has superb colour and greyscale contrast, down to the corners.

Economical and environmentally-friendly

The mercury-free backlight with efficient but bright, white LEDs is a particularly impressive feature of the EV2216W. It requires just 12 watts in regular use. This reduces energy costs and CO₂ emissions.

Auto EcoView

The EcoView sensor measures the light in the environment and automatically adjusts the display brightness accordingly. The image brightness is increased in a bright environment and reduced in the dark. Alternatively, you can manually select the desired image brightness. The user can also freely select the desired image brightness. The EcoView index indicates how environmentally friendly each setting is.

EcoView Sense

When it comes to power savings, the EV2216W excels thanks its EcoView Sense function. It switches the display on or off entirely automatically depending on whether the user is present in front of the screen. EcoView Sense detects the user's return even before the keyboard or mouse are touched. This means the display is always ready for operation, yet it does not waste any power while the user is away.

EcoView Optimizer

EcoView Optimizer analyses and responds to the white portion of the image content to control the display backlight. When the displayed content is dark, the light emission is reduced so that power consumption decreases by up to 30%. The image brightness defined by the user is nevertheless maintained at all times, as EcoView Optimizer also controls the hue values.

Eco Timer EIZO uses two methods to save energy: After a predefined time, Eco Timer automatically switches the monitor into standby mode, reducing power consumption. The power switch, located directly on the monitor, switches the power supply off completely and therefore minimises unnecessary CO₂ emissions as well as costs.

Precise colour control

Colour temperature control allows the white balance to be adjusted at intervals of 500 between 4,000 and 10,000 K. In addition, the colour saturation (gain) for RGB colours can be configured separately.

FineContrast

This function offers a wide range of display modes with various default settings for brightness, colour temperature and gamma. It provides ideal display configurations for office applications, Internet and images (sRGB) at the push of a button. The 'Paper' mode simulates the pleasing contrast and white balance of printed documents. In addition, two user modes are also available for customised settings.

Digital and analogue inputs

A DisplayPort and a DVI-D input enable the connection of a wide variety of digital signals. A D-Sub input is available for analogue signals. Up to three computers can be connected at the same time.

USB hub

An integrated USB hub enables the connection of peripheral devices. For example, a keyboard and mouse can be connected to the monitor right on the desk.

ScreenManager Pro for DDC


ScreenManager Pro is used for convenient monitor control using software via the Windows interface as an alternative to the on-screen display. The signal cable is all that is required for connection. It is even possible to link monitor settings to specific applications, for example, switching to sRGB display properties when opening the browser.

Audio-enabled

Speakers and headphone jack are discreetly integrated into the housing.

FlexStand

This enables turning and tilting as well as operation in portrait and landscape format. The continuous height adjustment starts very low near the desk and has a range of 14 centimetres. This guarantees optimal ergonomics, regardless of whether the user is sitting or standing in front of the screen. The FlexStand base is always fully stable, despite its maximum range of movement.



Test marks



EIZO Europe:



Austria ♦ www.eizo.at
Belgium & Luxembourg ♦ www.eizo.be
Czech Republic ♦ www.eizo.cz

Germany ♦ www.eizo.de
Hungary ♦ www.eizo.hu
Italy ♦ www.eizo.it

Slovakia ♦ www.eizomonitor.sk
The Netherlands ♦ www.eizo.nl
United Kingdom ♦ www.eizo.co.uk

EIZO EV2216W

Specifications

Diagonal	55.8 cm (22 inches) 16:10 aspect ratio
Models (housing colour)	EV2216WFS3-GY (light grey) EV2216WFS3-BK (black)
Visible image size	474 mm (width) x 296 mm (height)
Visible diagonal	558 mm
Ideal and recommended resolution	1680 pixels x 1050 lines
Dot pitch	0.282 mm x 0.282 mm
Displayed colours	16.7 million
Max. brightness	250 cd/m ² (typical)
Max. dark room contrast	1000:1 (typical)
Max. viewing angle	Horizontal: 170°; vertical: 160°
LCD technology	TN
Typical response time	5 ms black-white-black changeover
Features	EcoView Sense, Auto EcoView, EcoView Index, EcoView Optimizer, HDCP decoder, FineContrast, On-Screen Display, PowerManager by VESA DPMS, Plug & Play via VESA DDC CI, USB hub, integrated speakers and power supply
Configuration options	Minimum and maximum brightness, contrast, gamma, colour saturation for RGB, colour temperature, clock, phase, image position, resolution, Eco Timer, OSD language (DE, UK, FR, SE, ES, IT), interpolation
Resolutions	1680 x 1050 full image 1:1, 1280 x 1024, 1024 x 768, 800 x 600, 720 x 400, 640 x 480, enlarged to full image or 1:1
Horizontal frequency	31–68 kHz (digital: 31–68 kHz)
Vertical frequency	55–61 Hz (digital: 59–61 Hz)
Video bandwidth	146 MHz (digital: 119 MHz)
Graphic signals	DisplayPort, DVI (TMDS), RGB analogue
Signal inputs	DisplayPort, DVI-D and D-Sub
Plug & Play	VESA DDC CI
Power management	VESA DPMS, DVI-DMPM
Power consumption	max.* 39 watts, typically 12 watts, less than 0.3 watts in standby mode, 0 watts when power switch is OFF
Dimensions (WxHxD)	50 x (34 - 48) x (23) cm
Weight	5.6 kg
Test marks	CE, TÜV GS, TÜV certified ergonomics, TCO 6, Energy Star, ISO 9241-307 Class 1
Speakers	Left and right
Audio input	3.5 mm stereo jack
Audio output	3.5 mm stereo jack (for headphones)
Flexibility	172° right/left, -5° forward, 35° to the back, 90° rotatable, 14 cm height adjustment
USB hub	One upstream/two downstream, rev. 2.0
Accessories included	Manual in German, English and French, power and signal cables (DP-DP and DVI-D->DVI-D), ICC colour profile
Service	Five years on-site replacement service

Errors excepted 09/15

* at maximum brightness, USB hub as well as all signal inputs and speakers in operation



EIZO Europe:

Austria ♦ www.eizo.at
Belgium & Luxembourg ♦ www.eizo.be
Czech Republic ♦ www.eizo.cz

Germany ♦ www.eizo.de
Hungary ♦ www.eizo.hu
Italy ♦ www.eizo.it

Slovakia ♦ www.eizomonitor.sk
The Netherlands ♦ www.eizo.nl
United Kingdom ♦ www.eizo.co.uk